



SPECIFICATIONS :
 RATING : 30mA / 28VDC
 OPERATING SPEED: 10mm/sec
 ELECTRIC LIFE : 20,000 CYCLES
 FORCE 1 : 5-7N
 FORCE 2 : 11-14N
 OPERATING POSITION 1 : 9.7 ±0.2mm
 OPERATING POSITION 2 : 8.9 ±0.2mm
 FULL TRAVELS : 2.0mm

MATERIALS :
 PUSHER : POM BLACK
 DUST PROTECTION CAP : POM BLACK
 CASE : PA NATURE GLASS FIBER REINFORCED
 SPRING : PIANO WIRE
 CONTACT/TERMINALS : BRASS PLATED



TACLEX ELECTRONICS CO., LTD.

符號	變更紀錄	變更日期	SCALE (比例): 4:1	TITLE 圖名	SNAP ACTION SWITCH	SIZE 圖紙	A3	
1			TOLERANCE(公差): X.XX mm ± 0.25mm X.X mm ± 0.40mm ANGULAR: ± 2° FILE NAME: Mech041Asm-1	DWG NO. 圖號	Mech041Asm-1	UNIT 單位	mm	
2		REV. 版本		R05	DATE 日期	APR-13-2009	SHEET 張數	1
3		CHECKED BY 審核			DRAW BY 製圖	王柏堅		
4								
5								