



1	符號	原尺寸	修改後尺寸	變更日期
2	(A)			
3	(B)			
4	(C)			
5	(D)			
	(E)			

SCALE (比例): 3:1

TOLERANCE (公差):
 0.00 mm ± 0.25mm
 0.0 mm ± 0.40mm
 ANGULAR: ± 5°
 FILE NAME: PTC0001

SPECIFICATIONS :
 RATING : 100mA/32VDC MAX.
 CONTACT RESISTANCE : 250mΩ MAX
 INSULATION RESISTANCE : 100MΩ min, 500VDC
 DIELECTRIC STRENGTH : 250VAC for 1 Minute
 OPERATING LIFE : 25,000 cycles
 OPERATING TEMPERATURE : -40°C~85°C at 96% RH Max
 OPERATING FORCE : 400±120gf
 TOTAL TRAVELS : 2.4mm±0.3
 MAX POWER:1.0VA

MATERIALS :
 CASE : PA+GF
 ACTUATOR : PC
 SPACER : SILICON
 CONTACT/TERMINALS : GOLD PLATED BRASS



TACLEX ELECTRONICS CO., LTD.

TITLE		DIP PUSH SWITCH		SIZE	A4
DWG NO.		PTCT-07-A		UNIT	mm
REV.	DATE	SEP - 08 - 2010	SHEET	張數	1 of 1
CHECKED BY	DATE	SEP - 08 - 2010	DRAWN BY	製圖	IRENE
審核	RICHARD				