



TRAVEL	SWITCH POSITION
0°	C-C(OFF)
45°	C-1
90°	C-2
135°	C-3
180°	C-4
225°	C-5
270°	C-6
315°	C-7

SPECIFICATIONS

ELECTRICAL RATING: 0.5A 24VDC; 0.2A 48VDC
 CONTACT RESISTANCE:100mΩ MAX.
 INSULATION RESISTANCE:100MΩ MIN. 500VDC
 DIELECTRIC STRENGTH:Breakdown is not allowable;
 500VAC for 1 minute
 OPERATING FORCE: 350±100g
 OPERATING LIFE: 2,000 cycles
 PERATING TEMPERATURE RANGE : -20°C ~ 70°C

MATERIAL
 HOUSING: NYLON 6/6
 BASE:LCP
 ACTUATOR: NYLON 6/6
 TERMINAL: Brass gold plating.

P.C.B. LAYOUT



符號	原尺寸	修改後尺寸	變更日期
1 (A)		圖面重新整理	OCT-19-2010
2 (B)		增加註解與柄長7.80	OCT-25-2010
3 (C)		料號變更參照ECN N1037	DEC-02-2010
4 (D)			
5 (E)			

SCALE (比例) : 4 : 1

TOLERANCE (公差) :
 0.00 mm ± 0.25mm
 0.0 mm ± 0.40mm
 ANGULAR : ± 5°
 FILE NAME : RT0001

TITLE	圖名	ROTARY SWITCH	SIZE
DWG NO.	圖號	RT-0C8	圖紙
REV.	版本	D	UNIT
CHECKED BY	DATE	JAN-07-2010	mm
審核	RICHARD	DRAWN BY	SHEET
		製圖	張數
			1 of 1
			Jack_Lun