



### SPECIFICATION

**A: MATERIAL:**

1. HOUSING: NYLON 66 FLAMMABILITY, UL 94V-0
2. TERMINAL: COPPER ALLOY, TIN PLATED

**B: CHARACTERISTICS:**

1. RATING: 10A 250V~ NORTH AMERICA & EUROPE
2. INSULATION RESISTANCE: 100 MΩ MIN, AT 500 V DC
3. ELECTRIC STRENGTH: AC 2,000 V FOR 1 MINUTE

**C: APPROVALS:**

UL, CUL, CSA, VDE, ENEC, KC & CCC

暫行使用章

	<b>PART NO.:</b> 0717-1-PQ	<b>NAME:</b> AC INLET 3P+ FUSE HOLDER (PUSH-IN)
	<b>MATERIAL:</b> SEE ABOVE	<b>SPEC.:</b> IEC 60320-1, C14 IEC 60127-6
<b>TOLERANCE UNLESS OTHERWISE MARKED</b>		<b>APPROVED CHECKED DESIGNER NOTE:</b>
<b>DIMENSION:</b> .000: ±0.1 .00 : ±0.2 .0 : ±0.3		 2012-05-10 王 2012-05-10 泉永 0717-0007
<b>ANGULAR:</b> ±3°		
<b>UNIT</b> mm	<b>SCALE</b> 1:1	<b>SHEET</b> 1 of 1

REV	DATE	DOCUMENT	DESCRIPTION
M			
L			
K			
J	2012.03.20	DGRXXXXX	CHANGE SAFETY MARK
I	2006.04.17	DGR06030	DIMENSIONS & MARKING CHANGE
4			