

開關構造說明 (Switch Construction Instructions)

照光緊急停止開關 (Illuminated Emergency Stop Switches)

照光緊急停止開關操作部
(Illuminated Emergency Stop
Switches Operators)
Page.120



照光緊急停止開關
Emergency Stop
Page.23



燈泡
(Lamp)
Page.141



接點塊
Block
Assemblies)
Page.137-140



接點塊安裝轉接器
(Contact Block
Mounting Adapter)
Page.140



接點塊
(Contact Block)
Page.139



全電壓轉接器
(Full Voltage
Adapter)
Page.140



接點塊
(Contact Block)
Page.139



照光緊急停止開關 (Illuminated Emergency Stop Switches)


φ 40mm 蘑菇頭形 (Mushroom φ 40mm)

20L



燈泡 (Illumination Type)	動作類型 (Operation)	接點結構 (Contacts)	型號 (Type No.)	使用電壓記號③ (Operating Voltage Code ③)	顏色記號 (Lens Color Code)
無 (Without Lamp)	按鎖定拉出 或旋轉復歸 (Pushlock Pull/Turn Reset)	1NO	A20L-V4E10Q0R	0 (無燈泡) (Without Lamp) 最大(max.) 250V AC/DC	僅紅色 (Red only)
		1NC	A20L-V4E01Q0R		
		2NO	A20L-V4E20Q0R		
		2NC	A20L-V4E02Q0R		
		1NO-1NC	A20L-V4E11Q0R		
LED		1NO	A20L-V4E10Q③R	2 (6V AC/DC) 3 (12V AC/DC) 4 (24V AC/DC) H (110V AC/DC) M3 (230/240V AC/DC)	內置LED : LAED-③R (Built-in LED lamp)
		1NC	A20L-V4E01Q③R		
		2NO	A20L-V4E20Q③R		
		2NC	A20L-V4E02Q③R		
		1NO-1NC	A20L-V4E11Q③R		
白熾燈泡 (Incandescent)	1NO	A20L-V4E10Q③R	5 (6V AC/DC) 6 (12V AC/DC) 7 (24V AC/DC)	內置白熾燈泡 : LA-T③R (Built-in incandescent lamp)	
	1NC	A20L-V4E01Q③R			
	2NO	A20L-V4E20Q③R			
	2NC	A20L-V4E02Q③R			
	1NO-1NC	A20L-V4E11Q③R			

■外型尺寸(Dimensions) mm



面板厚度 (Panel Thickness)
0.8~6

