



NO. POLES	MODEL NO.	SWITCH FUNCTION			TERMINAL QUANTITY	CONNECTED TERMINALS		
		POS.1	POS.1	POS.1		POS.1	POS.1	POS.1
SPDT	PL704-1	ON	NONE	ON	3P	1-2	—	2-3
SPDT	PL704-1A	MM	NONE	ON	3P	1-2	—	2-3

MM=MOMENTARY

SPECIFICATION

- 1.PATING:10A 250VAC,15A 125VAC
15A 250VAC,20A 125VAC
- 2.INSULATION RESISTANCE:DC 500V 200MΩ OR MORE
- 3.CONTACT RESISTANCE:DC 2-4V 1A 20MΩ OR LESS
- 4.WITHSTAND VOLTAGE:AC 1500V OR MORE

端子種類尺寸 Termination Options

H1	H2	H3	H4	H5
<p>MADE IN TAIWAN</p> <p>7.2</p> <p>7</p>	<p>MADE IN TAIWAN</p> <p>9.2</p> <p>6.8</p>	<p>MADE IN TAIWAN</p> <p>5.1</p> <p>4.8</p>	<p>MADE IN TAIWAN</p> <p>10.6</p> <p>4.8</p>	<p>MADE IN TAIWAN</p> <p>10.3</p> <p>6.3</p>

品名 PRODUCT	POWER TOGGLE SWITCH				
比例 SCALE	1:1	單位 UNIT	MM	公差 TOLERANCE	