



Operating Pressure:1600gf ±300gf
 Operating Stroke:2.8mm±0.3
 Function:(ON)-OFF
 Body:PP,UL rated:94V-2 Black
 Pluger:PP,UL rated:94V-2 Black
 Terminal:Brass, Gold plate
 Rating: 3A 18V DC
 Contact Resistance: 50mΩ MAX
 Insulation Resistance: 100MΩ MIN
 Dielectric Strength: 1500VAC 1 minute
 Electrical life: 10,000 cycles
 Mechanical life :75,000 cycles
 Operating Temperature: -30°C~80°C
 Relative Air Humidity:45%~85%

轩立电子（深圳）有限公司

公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE±1° 单位 DIMENSION UNIT mm.

版本 VERSION	A0	比例尺 SCALE	1:1	日期 DATE	2021.09.08	品名 TITLE	图号 DRAWING NO
------------	----	-----------	-----	---------	------------	----------	---------------

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	孙成	黑色按钮开关	FD-04
--------	-------------------------	---------	---------	----------------	---------------	-------------	----	--------	-------