



SPECIFICATIONS

RATING: DC12V,3A
 CONTACT RESISTANCE: 100mΩ MAX.
 INSULATION RESISTANCE: 1000MΩ MIN.
 DIELECTRIC STRENGTH: 1000Vrms min.
 OPERATING FORCE: 1200gf min.
 OPERATING TEMP: -40°C~+85°C
 MECHANICAL LIFE: 75,000 CYCLES
 RoHS & Lead Free

MATERIALS

HOUSING: Nylon, Gray.
 PLUNGER: PBT, Gray.
 CASE: Nylon, Gray.

RECOMMENDED MOUNTING HOLE

轩立电子（深圳）有限公司

符號	原尺寸	修改後尺寸	變更日期	SCALE (比例) : 1 : 1	TITLE 圖名	PLUNGER SWITCH			SIZE 圖紙
1	(A)			TOLERANCE (公差) : 0.00mm±0.25mm 0.0mm±0.40mm ANGULAR: ±5° FILE NAME : DSH0002	DWG NO. 圖號	FD-02			UNIT 單位
2	(B)				REV. 版本	A	DATE 日期	MAR - 16 - 2021	SHEET 張數
3	(C)				APPROVE 審核	顧睿豐	CHECK 確認	蔡揮騰	DRAW 製圖
4	(D)								IRENE
5	(E)								