

TYPE-C 防水母座12P沉板带勾两脚不外露

XL-ATCF-12-003

30 Min/1.5M IP-X8

Technical drawings showing dimensions: 8.35^{+0.05}/_{-0.03}, 2.56^{±0.04}, 7.60, 6.40, 2-0.80, 2-0.50, 7-0.50, 8-0.35, 4-0.50, 1.55, 0.66, 3.30, 2.70, 8.20, 2.68, 9.05, 0.50, 1.10, 11.30. RECOMMEND P.C.B LAYOUT (COMPONENT SIDE) TOLERANCE FOR PCB LAYOUT IS ±0.05

TYPE-C 12P母座 防水拉伸 沉板四脚L=7.65 SMT外露1.0

XL-ATCF-12-004

30 Min/1.5M IP-X8

Technical drawings showing dimensions: 8.35^{+0.05}/_{-0.02}, 7.65, 5.45, 1.45, 1.00, 4*0.40, 8*0.23, 6*0.50, 2*0.25, 2*0.65, 2*0.80, 17.50, 9.05, 4*0.50, 8*0.35, 4*1.10, 4*0.50, 2*3.30, 2*2.70, 4.00, 2*1.10, 11.30, 0.95, 1.20, 4.40, 2.50. UNRECOMMENDED PCB LAYOUT (TOP VIEW) THICKNESS 0.8±0.10MM DEFAULT TOLERANCE: ±0.05

TYPE-C-14P 立贴防水母座H=9.3-10.0mm

XL-ATCF-14-001

30 Min/1.5M IP-X8

Technical drawings showing dimensions: 8.34^{+0.06}/_{-0.02}, 2.56^{±0.04}, 9.30, 10.55, 8.94, 5.05, 3.16, 2.40, 0.27, 8.40, 14-1.00, 1.00, 0.60, 1.50, 1.10, 1.00, 14-0.32, 4.74, 6.00, 2-0.70, 4.66. RECOMMEND P.C.B LAYOUT (COMPONENT SIDE) TOLERANCE FOR PCB LAYOUT IS ±0.05

TYPE-C 16母座防水IPX8板上贴板 后脚插L=6.5舌头外露 0.95 (粉末金外壳)

XL-ATCF-16-001

30 Min/1.5M IP-X8

Technical drawings showing dimensions: 6.50, 1.00, 0.95, 1.10, 0.40, 8.90, 4.00, 0.40, 10.44, 9.04, 8.34^{+0.06}/_{-0.02}, 2.56^{±0.04}, 3.26, 4.66, 6.40, 4.80, 8-0.30, 4-0.60, 1.10, 3.05, 0.50, 3.50, 2*0.90, 1.60, 2.00, 1.10, 4.00, 8.90, 1.60, 1.10. RECOMMEND P.C.B LAYOUT TOLERANCE UNSPECIFIED ±0.05mm

TYPE-C 16P母座 防水IPX8沉板0.8 / 1.2 / 1.6 L=6.5舌头外露0.95 (粉末金外壳)

XL-ATCF-16-002/003/004

30 Min/1.5M IP-X8

Technical drawings showing dimensions: 6.50, 1.00, 0.95, 0.80, 2.00, 0.40, 1.00, 0.37, 0.50, 10.44, 9.04, 8.34^{+0.06}/_{-0.02}, 2.56^{±0.04}, 3.26, 4.66, 2.60, 10.65, 4-0.60, 8-0.30, 0.50, 3.50, 4.80, 6.40, 2.65, 2.50, 3.65, 9.70, 10.95, 12.80. RECOMMEND P.C.B LAYOUT TOLERANCE UNSPECIFIED ±0.05mm

防水TYPE-C-USB AF
防水Micro USB
TYPE-C F 2P / 4P
TYPE-C F SERIES 4P / 6P
TYPE-C F 14P / 16P
TYPE-C F 24P
TYPE-C M公头
Micro USB母座
USB 3.0母座
USB A型公头
HDMI-DP/Lighting